

CASCADE LASER CORPORATION

Portable RF Wattmeter Model 4304A

Product Information



Figure 1: Model 4304A

Notable Features:

- 25-1000 MHz 5-500 Watt Element
- Field Ready
- Easy to use
- Rugged & Reliable

Product Specifications:

Accuracy:	25-100 MHz, +/-7% of full scale, using correction charts, 100-512 MHz, +/-6% of full scale, no correction needed, 512-1000 MHz, +/-7% of full scale, no correction needed
Frequency Range:	25 MHz to 1.0 GHz
Connector:	QC Type (Female N normally supplied)
Insertion Loss:	25-521 MHz, 0.10 dB max with UHF female conn., 512-1000 MHz range, 0.13 dB max.
Insertion VSWR:	25-521 MHz, 1.05 max. (with UHF female conn.), 512-1000 MHz range, 1.07 max.
Power Range:	5, 15, 50, 150, 500 W, with no scale limitations except power limited to 150 W from 800-1000 MHz
Weight:	3 lbs. (1.36 kg)
Nominal Size:	6-7/8"H x 5-1/8"W x 3-5/8"D (175 x 130 x 92 mm)
Finish:	Light gray powder coat

Contact Cascade Laser Corporation for ordering information or to request a quotation on any of these products.

Cascade Laser Corp.

101 N. Elliott Rd.

Newberg, OR 97132

Phone: 503-554-1926

Toll Free: 800-443-5561

Fax: 503-554-8285

E-mail: info@cascadelaser.com

Web: www.cascadelaser.com

*Portable RF Wattmeter - Model 4304A
December 2003*